

TECHNICAL DATA

X8 VT-DRIVE		X8.631 VT-DRIVE
Max power (ISO TR 14396)	hp / kW	305 / 224
Max torque at 1400 rpm	Nm	1247
Manufacturer		FPT
Engine type - Installation		NEF 67 - iso-mounted on cast iron chassis
Cylinders / Displacement / Valves		6 / 6.7 l / 24
Type		VT-Drive - continuously variable transmission
No. of stages		4
Transmission control		EasyPilot with multifunction armrest
Speeds		540 E / 1000 / 1000 E
Front suspended axle		● front parallelogram suspension system (PREMIUM version)
Hydraulic piston pump with CCLS system - flow rate		● 160 l/min
Rear remote valves - type, flow rate, min - max		electrohydraulic, 140 l/min, 4 - 6
Max lifting capacity at hitch points	kg	12000
Max lifting capacity at 610 mm	kg	5000
Type		○ electrohydraulic multidisc clutch with modulated engagement
Première Cab - 4-post cab with McCormick mechanical suspension		●
McCormick semi-active suspension system		● electronically-controlled electrohydraulic semi-active cab suspension
EasyPilot with multi-function armrest		●
DSM Data Screen Manager		● 12" touch screen monitor
PSM Precision Steering Management, rear ISObus & EazySteer - ready		●
PSM Precision Steering Management, rear ISObus & EazySteer		○ EGNOS full kit ○ RTK NTRIP full kit - AT Spare Parts
McCormick Fleet & Remote Diagnostics Management and Farm Management Pro Pack		on selected markets - ● 1 year - ○ 3 years - ○ 5 years
Wheelbase	mm	3000
Shipping weight - measured with average specs	kg	11000
Gross vehicle weight	kg	16000
Max front and rear tyre sizes (Index Radius - IR)	mm	650/65R34 (IR 775) - 900/60R42 (IR 1025)

Key: ● standard ○ option