


DIMENSIONS		CROP DIVIDER	
Overall Length (mm)	11464	Distance Between the Tips	1100 mm / 43.3 inch
Overall Width (mm)	2500	Lower Section	Hardened Shoe
Overall Height (mm)	3792	Height Adjustment	Hydraulic
Weight (kg/lbs)	8560 / 18,872	Spiral Angle Degree	30° - 32°
Min. Ground Clearance (mm)	180/320 (at lowest/highest cylinder)	FEED ROLLERS	
Min. Turning Radius (mm)	5500	Number of Rollers	11
ENGINE		No. of Rollers on Roller Train	8
Make	Cummins	Drive	Hydraulic & Reversible
Series	B 5.9	Upper Rollers	Floating
Power	173 HP	CHOPPER	
Cylinder Volume	5.9 Liters	Number of Knives per Drum	3
Number of Cylinder	6	Deflector Plates	Adjustable
Aspiration	Turbo/Air Cooled	KNOCKDOWN ROLLER	
TRANSMISSION		Height	Adjustable
Type	Hydrostatic	Angle Degree	50°
Travel Speed (kmph/mph)	Variable upto 15 / 9	EXTRACTOR	
CAPACITY		Number of Blades	3
Fuel Tank (L/imp. gal)	208 / 45.8	Hood	Directional
Hydraulic Oil Tank (L/imp. gal)	130 / 29	ELEVATOR	
TYRES		Drive	Hydraulic & Reversible
Front	10.5 / 65-16, 14 PR	Turning Angle	168°
Front Pressure	4.14 bar / 60 psi	Weight	<b>TOPPER</b> 8300 Kg
Rear	16.9 / 28, 12 PR	Height Variation(mm / inch)	1050-2800 / 41.3-110.2
Rear Pressure	3.1 bar / 45 psi	Height Adjustment	Hydraulic

The company reserves absolute rights to modify the specifications of machine and components there in without any prior notice.  
Accessories shown are not a part of standard equipment.




**ADVANCED TRACKING SYSTEM**



**AUTO CLEANING SYSTEM**



**CONTROL PANEL**



**DOUBLE CROP DIVIDER**




**ENGINE ASSEMBLY**



**(MAIN)BASE CUTTER**



**FAN ASSEMBLY**



**HYDRAULIC SYSTEM**



**OPERATOR CABIN**



**ROOFTOP AC**



**STABILITY**



**VISIBILITY**